

# Desktop Card Embosser

By NBS Technologies

## Advantage™ M8

EMV Compliant

The new Advantage™ M8 Instant Issuance embosser is the ideal solution that allows real flexibility and security in instant card issuance. This all-in-one solution allows the user to encode magnetic stripe, program smart chip, print (mono or color), emboss/indent and tip in one pass.

The Advantage™ M8 makes it easy to issue financial or loyalty cards in a very secure environment to customers for immediate use. The Advantage™ M8 features the unique card input matrix which can hold a total 750 cards using 5 separate cassettes with 3 card hoppers per cassette capable of holding 50 cards each. All cassettes have key lock security to provide the highest level of protection for the card stock.



## THE MOST FLEXIBLE SOLUTION FOR BANK AND RETAIL DESKTOP FINANCIAL INSTANT ISSUANCE CARDS



### XPRESSI INSTANT ISSUANCE

The Advantage M8 embosser combined with Xpressi instant issuance software, creates a total and scalable solution for financial institutions to easily generate secure EMV data and personalize their customer cards for immediate distribution at the local branch level.

## THE ADVANTAGE™ M8 OFFERS THESE KEY FEATURES AND BENEFITS:



### ENHANCE THE CUSTOMER EXPERIENCE

- Reduce customer wait times from weeks to minutes
- Maximize customer face time in your financial location



### INCREASE SECURITY AND RISK MITIGATION

- Eliminate card delivery failure due to theft
- Reduce fraud impact of stolen cards
- Anchors for bolting down the embosser to its operating station



### INCREASE REVENUE OPPORTUNITIES

- Create account lift with instantly available cards
- Enjoy “top of wallet” benefit with unique personalization capabilities
- Increase opportunities to cross sell other financial products



## Embosser Specifications

<b>Card Type</b>	ISO 7810, 7811 - 1/2/6 PVC card ISO 7816-1/2/-3 (Class A and Class B)/EMV4.0 approved. This card must be free of burrs, bumps and scratches
<b>Magnetic Stripe</b>	ISO 7811-2(Low coercivity), 7811-6(high coercivity)
<b>Smart Card (optional)</b>	Contact Smart Card - USB connection PCSC coupler from rear
<b>Emboss</b>	Emboss font capacity: 54 characters (Max 80 character including indent font) Variety of emboss fonts: Alpha(10 CPI) A-Z : 26 Num(10 CPI) 0-9 : 10 Num(7 CPI)(OCR-7B) 0-9 : 10 Symbol(10 CPI) - / . ' , ( ) & : 8
<b>Front and Rear Indent (optional)</b>	Rear indent font: OCRB1 0-9; OCRA 0-9 : 10 Indent Film Detection: Mastercard 0-9; Helvetica 0-9 Ribbon-end detection
<b>Tipper</b>	Tipping foil color: Silver, Gold Tipping Foil Detection: Foil-end detection
<b>Printer (optional)</b>	Print Mode: Color (Dye-sublimation), Mono (Thermal transfer) Print Resolution: 300 dpi Print Side: Dual side
<b>Input (optional number of cassettes - 0 to 5)</b>	Input Methods: Automatic or Exception Feed Number of cassette / hopper: 5 cassette / 15 hopper (3 hoppers per cassette) Machine can be configured with 0 to 5 cassettes Input Hopper Capacity: 50 cards / hopper (750 cards total) Security: Software and key lockable hopper cassette Card presence detection: Out of Card detection
<b>Output Stacker</b>	Output stacker capacity: Approximately 20 cards Security: Software lockable output stacker Card presence detection: Card full detection
<b>Rejected Cards</b>	Reject stacker capacity: Approximately 25 cards Card presence detection: Card-full detection
<b>Card Counter</b>	Resettable: Software counter Non-resettable: Mechanical counter
<b>Machine Throughput</b>	58 seconds (Mag encode, Emboss, Rear Indent, Tip) 64 seconds (Print Mono, Mag encode, Emboss, Rear Indent, Tip) 81 seconds (Print Color, Mag encode, Emboss, Rear Indent, Tip) Smart card encoding times not included - speed varies based on card specifications
<b>Dimension</b>	Machine: 380mm (15") (W) x 660mm (26") (H) x 780mm (31") (D) Machine with anchor plate: 456mm (18") (W) x 660mm (26") (H) x 780mm (31") (D)
<b>Weight</b>	85 kg / 187.63 lbs
<b>Connection Interface</b>	Ethernet and USB (cable 3m in length or less)
<b>Warranty</b>	12 months
<b>Display</b>	LCD display (16 characters per line)
<b>Applicable Standard</b>	2004/108/EC, EN55022:2013, FCC 47CFR PT 15 SPT, EN55024:2010
<b>Security</b>	° All Access Doors under key lock ° Software lock (optional) for front cover (allows for software log of operator who opened front door) ° Hopper cassette key lock ° Mechanical bolt down capability ° Kensington lock compatible
<b>Power</b>	Rated power: 100-120VAC 4.5A / 220-240VAC 3.0A Rated frequency: 50-60Hz



Contact our NBS card personalization experts for full details on this and other card personalization products at:

Global Headquarters  
10925 Bren Road E  
Minneapolis, MN 55343  
USA  
tel: +1 952.912.9400  
fax: +1 952.912.9439  
email: info@nbstech.com

B1 Moorfield Point  
Slyfield Industrial Park  
Guildford, Surrey GU1 1RU  
United Kingdom  
tel: +44 (0)1483 563200  
fax: +44 (0)1483 511189  
email: javelin@nbstech.com

20614 Eastleigh Crescent  
Langley BC V3A 4C4  
Canada  
tel: +1 604.530.6012  
fax: +1 604.530.9685  
email: info@nbstech.com